



WESTPOINT®
Create emotions



ACS

WALL SPLIT AIR CONDITIONER INVERTER COOL AND HEAT PUMP

CLIMATISEUR SPLIT MURAL INVERTER REVERSIBLE
AIRE ACONDICIONADO TIPO SPLIT INVERTER FRÍO Y CALOR

T1 R32 220-240 V - 1 PH 50 Hz

A++



WIM-09220.MH
Cap 9000 BTU

A++



WIM-12220.MH
Cap 12000 BTU

A++



WIM-18218.MH
Cap 18000 BTU

A++



WIM-24218.MH
Cap 24000 BTU

Specifications are subject to possible modifications without prior notice. Pictures and datas are not contractual / Les caractéristiques sont susceptibles d'être modifiées sans préavis. Les photos et indications sont non contractuelles / Las especificaciones están sujetas a cambios sin previo aviso. Las fotografías e indicaciones están no contractuales.



		WIM-09220.MH	WIM-12220.MH	WIM-18218.MH	WIM-24218.MH
T1 Cooling capacity	(Btu)	9000	12000	18000	24000
	(W)	2637	3516	5275	7032
	(frig/h)	2250	3000	4500	6000
T1 Heating capacity	(Btu)	10000	13000	19000	25000
	(W)	2930	3809	5569	7325
	(frig/h)	2500	3250	4750	6575
T1 Cooling mini/maxi	(W)	908-3400	1114-4162	1817-6125	2080-7948
	(Btu)	3100-11600	3800-14200	6200-20900	7100-27120
T1 Heating mini/maxi	(W)	820-3370	1080-4420	1377-6125	2081-7948
	(Btu)	2800-11500	3700-14400	4700-23000	5500-30000
Input power cooling	(W)	732	1213	1539	2345
Input power heating	(W)	733	1088	1480	2035
Rated current cooling	(A)	3.18	5.27	6.9	10.2
Rated current heating	(A)	3.18	4.73	6.4	10.2
Moisture removal	(L/h)	0.8	1.1	-	-
Air flow	(m3/h)	466/360/325	540/430/314	840/680/540	980/817/662
Remote control		Yes	Yes	Yes	Yes
Inverter		Yes	Yes	Yes	Yes
Gas refrigerant		R32	R32	R32	R32
Charge	(g)	550	550	1000	1600
SEER		6.3	6.1	7.1	6.1
Energy class		A++	A++	A++	A++
SCOP		4.0	4.0	4.0	4.0
Energy class		A+	A+	A+	A+
Voltage	(IDU V-Ph)	220-240 V - 1 PH	220-240 V - 1 PH	220-240 V - 1 PH	220-240 V - 1 PH
	(ODU V-Ph)	220-240 V - 1 PH	220-240 V - 1 PH	220-240 V - 1 PH	220-240 V - 1 PH
Frequency	(Hz)	50 Hz	50 Hz	50 Hz	50 Hz
FEATURES					
Indoor unit					
Net dimensions	height - (mm)	285	285	302	327
	width - (mm)	805	805	957	1040
	depth - (mm)	194	194	213	220
Net weight	(kg)	7.6	7.6	10	12.3
Sound pressure	high - (dBA)	38.5	40.5	44	59
	medium - (dBA)	32	34.5	37	42
	low - (dBA)	25	25	30	28
Rated current	(A)	10	10	13.5	17.5
Rated input	(W)	2150	2150	2950	3850
Outdoor unit					
Net dimensions	height - (mm)	495	495	554	702
	width - (mm)	720	720	800	845
	depth - (mm)	270	270	333	363
Net weight	(kg)	23.2	23.2	34	51.9
Noise level	(dBA)	55.5	56	56	59.5
Compressor type		ROTARY	ROTARY	ROTARY	ROTARY
Connection pipe	maxi length allowed - (m)	25	25	30	50
	diameter liquid - (mm inch)	6.35 (1/4)	6.35 (1/4)	6.35 (1/4")	9.52 (3/8")
	gas connexion - (mm inch)	9.52 (3/8)	9.52 (3/8)	12.7 (1/2")	15.9 (5/8")
OPTIONS					
Timer	(h)	24	24	24	24
STANDARD					
CE Standard		CE	CE	CE	CE
RoHS Standard		RoHS	RoHS	RoHS	RoHS