# Trouble Shooting Guide
# Guide des Codes Erreurs

## WNPPY-153B21.F3
## R290

**Updated on: 06 MAY 21**

Specifications are subject to possible modifications without prior notice. Les présentes spécifications sont susceptibles d'être modifiées sans préavis. Las especificaciones estàn sujetas a cambios sin previo aviso

# Trouble Shooting Guide – Guide des Codes Erreurs
# WNPPY-153B21.F3

**Troubleshooting**

Refrigerator stops working (light off):

☆ Power supply failure

▲ Remedies:

☆ Check that the plug is inserted properly in the socket

☆ Check that the switch on/off

☆ Check that the mains voltage powers the plug

Refrigerator temperature go up:

☆ Unit to near to a heat source

☆ Condenser dirty or close

▲ Remedies:

☆ Move the counter or the heat source further away

☆ Clean the condenser

When replace the lamp,please turn off the power,and remove the screw of the lampshade with a screwdriver and replace the broken bulb with a new one which applys the same electrical parameter.

| A | ALARM PARAMETERS | | | | | | |
|---|---|---|---|---|---|---|---|
| A0 | Alarm and fan differential | C | -20.0 | 20.0 | 2.0 | °C/°F | . |
| AL | Low temperature alarm threshold/deviation (AL= 0; alarm disabled) | F | -50.0 | 150.0 | 0 | °C/°F | . |
| AH | High temperature alarm threshold/deviation (AH= 0; alarm disabled) | F | 50.0 | 150.0 | 0 | °C/°F | . |
| Ad | Low and high temperature alarm delay | C | 0 | 199 | 0 | min | . |
| A4 | Digital input configuration<br>0= input not active;<br>1= exter. alarm, instant (A7= 0) or delayed (A7>0);<br>2= enable defrost (open=disabled);<br>3= start defrost on closing;<br>4= curtain switch or night-time operation (open= normal setpoint);<br>5= remote ON/OFF (open= OFF);<br>6= AUX output control [H1=3] (open = AUX de-energ.);<br>7= AUX output [H1=3] + FAN OFF control (closed) (open = AUX energised);<br>8= AUX output [H1=3] + FAN-OFF (closed) + COMP-OFF control (closed); (open= AUX energised);<br>9= select direct/reverse operation: r3=0 => open= direct + defrost; closed= reverse r3=1/2 => open= direct; closed= reverse<br>10= condenser probe;<br>11= product probe | C | 0 | 11 | 0 | - | . |
| A7 | External alarm detection delay | C | 0 | 199 | 0 | min | . |
| A8 | Enable alarm 'Ed': end defrost by timeout (1= enabled) | C | 0 | 1 | 0 | - | - |
| Ac | High condenser temperature alarm | C | -50.0 | 150.0 | 70.0 | °C/°F | . |
| AE | High condenser temperature alarm differential | C | 0.1 | 20.0 | 5.0 | °C/°F | . |
| Acd | High condenser temperature alarm delay | C | 0 | 250 | 0 | min | . |